Product Comparison

Features		Regular	Ultimate
	Strength Strength is measured as the amount of force that the screen can withstand. We tested our screens to the limit.	Withstand impacts up to 400 ft-lbs of force	Withstand impacts up to 550 ft-lbs of force
	Fastening method How the mesh is secured into the screen frame	Tamper resistant screws	Double the amoun as the Regular
	Warranty Years of protection covered under your Crimsafe warranty	10	10
	Mesh Crimsafe Tensile-Tuff® stainless steel mesh is 26.5% thicker than typical stainless steel mesh	0.9mm Tensile-Tuff® 304 structural grade	0.9mm Tensile-Tuf 304 structural grac
Ċ	Clamping System System used to secure mesh into the frame	Exclusive Screw-Clamp™ technology	Exclusive Screw-Clamp™ technology
	Locking options Can be mechanical or electronic (allowing access by Keypad, Bluetooth or Keyfob)	Mechanical	Mechanical
	Locking points Number of secure points where the door locks into the frame	3	3



	iQ
S	Withstand impacts up to 880 ft-lbs of force
nt	Double the amount as the Regular
	10
f® de	0.9mm Tensile-Tuff® 304 structural grade
	Exclusive Screw-Clamp™ technology
	Mechanical or Electronic
	6 or 10

Technical Detail



Specifications	Regular	Ultimate	iQ
Impact Strength Testing	Up to 400ft-lbs*	Up to 550ft-lbs*	Up to 880ft-lbs*
Estimated Price Range	\$\$	\$\$\$	\$\$\$\$
Smart Entry and Exit Features optional			\checkmark
Tamper Resistant Screws and Hardwear	\checkmark	\checkmark	\checkmark
Anti-lift Pins			\checkmark
Heavy-duty Hinges			\checkmark
Custom designed to your needs	\checkmark	\checkmark	\checkmark
AS Powder Coating Standards	\checkmark	\checkmark	\checkmark
Emergency Exit Features	Yes	Yes	No
Insect Protection	\checkmark	\checkmark	\checkmark
UV Protection	Up to 62%	Up to 62%	Up to 62%
Solar Heat Gain Prevention	Up to 53%	Up to 53%	Up to 53%
Locking Points	3	3	6 or 10
Mesh Rating	Tensile-Tuff [®] 0.9mm 304 structural grade	Tensile-Tuff [®] 0.9mm 304 structural grade	Tensile-Tuff [®] 0.9mm 304 structural grade
Jimmy Resistant	\checkmark	\checkmark	\checkmark
Knife Shear Test Pass	\checkmark	\checkmark	\checkmark
Corrosion Resistance - (Salt Spray and Prohesion Accelerated Test)	3,000 Hours	3,000 Hours	3,000 Hours
Fall Prevention Suitable		\checkmark	\checkmark
Build-out	Optional	Optional	As standard
Midrail	\checkmark	\checkmark	\checkmark
Brushfire Protection	\checkmark	\checkmark	\checkmark
Hurricane Rating		✓ Protects from debris up to 150mph	
Fire attenuation	Crimsafe has products that are suitable for Fire Attenuation purposes. Please contact us for further information.		

*All framing ranges are available in 3 color options to best suit your home and lifestyle. All mesh is in black to boost visibility and reduct heat gain.

Applications	Regular	Ultimate	iQ
DOORS			
Hinged	\checkmark	\checkmark	\checkmark
Sliding	\checkmark	\checkmark	
Stacking	\checkmark	\checkmark	
French	\checkmark	\checkmark	
Bi-Fold		\checkmark	
WINDOWS	\checkmark	\checkmark	
Safe S Cape Inward or outward swinging	\checkmark	\checkmark	
Fixed	\checkmark	\checkmark	
OUTDOOR			
Hurricane		\checkmark	
Brushfire		\checkmark	